

ARTIFICIAL DISC PROSTHESIS

By Richard R. Navarro, 10350 Forestview Drive, Strongsville, Ohio 44136

Bharadwaj Ananthan, 367 Power Street, Akron, Ohio 44311

Randall R. Theken, 1100 Nola Avenue, Coventry Township, Ohio 44203

BACKGROUND OF THE INVENTION

1. Field of the Invention

[0001] This invention relates to an artificial visco-elastic, constrained motion disc for replacing intervertebral discs in the lower back, particularly in the lumbar and lumbar-sacral regions.

2. Background

[0002] The human spine is composed of many vertebral bones stacked one upon the other, with an intervertebral disc between each pair of adjacent vertebral bones. The discs act as cartilaginous cushions and shock absorbers. The spinal cord runs in a bony canal formed by successive openings in these bones. The spinal nerves exit the spinal cord between pairs of vertebrae and supply nerves and nerve signals to and from other body structures.

[0003] The intervertebral disc is a complex joint both anatomically and functionally. It is composed of three component structures: the nucleus pulposus; the annulus fibrosus, and the vertebral endplates. The biomedical composition and anatomical arrangements within these component structures are related to the biomechanical function of the disc.

[0004] The nucleus pulposus, occupying about 25% to 40% of the total disc cross-sectional area, usually contains approximately 70% to 90% water by weight. Because of this high water content, the nucleus may be mechanically described as an incompressible hydrostatic material.

[0005] The annulus fibrosus is a concentrically laminated structure which contains highly aligned collagen fibers and fibrocartilage embedded in an amorphous ground substance. The annular layers are oriented at approximately +/- 60° to the longitudinal axis of the spine. The annulus fibrosus usually contains approximately 8 to 12 layers, and is mechanically the main stabilizing structure which resists torsional and bending forces applied to the disc.

[0006] The two vertebral endplates separate the disc from the adjacent vertebral bodies, and are composed of hyaline cartilage.

[0007] Spinal discs may be damaged or displaced due to trauma or disease. In either case, the nucleus pulposus may herniate and protrude into the vertebral canal or intervertebral foramen. This condition is known as a herniated or "slipped" disc. The disc may in turn press upon the spinal nerve that exits the vertebral canal through the partially obstructed foramen, causing pain or paralysis in the area of its distribution. The most frequent site of occurrence of a herniated disc is in the lower lumbar region. To alleviate this condition, two procedures are common.

[0008] First, it may be necessary to remove the involved disc surgically and fuse the two adjacent vertebrae together. Spinal fusion is a good method of eliminating symptoms, but at the expense of total loss of motion of the fused vertebral joint, as well as increased stress in the adjacent segments. In many long-term patients of fused-spinal segments, a detrimental phenomenon has been observed whereby discs adjacent to the fused-spinal segment will have increased motion and stress due to the increased stiffness of the fused segment. This is sometimes referred to as "cascading spine syndrome," where previously normal motion segments above or below a fused segment exhibit spondylolisthesis, or degenerative disc disease due to increased loading.

[0009] A second method for alleviating disc problems is insertion of an intervertebral disc replacement. The object of an intervertebral disc replacement is to provide a prosthetic disc that combines both stability to support the high loads of the patient's vertebrae and flexibility to provide the patient with sufficient mobility and proper spinal column load distribution. In attempting to satisfy these competing design requirements, basically four types of artificial intervertebral discs have been developed: elastomer discs, ball and socket discs, mechanical spring discs, and hybrid discs.

[0010] Elastomer discs typically include an elastomer cushion which is sandwiched between upper and lower rigid endplates. Elastomer discs can provide cushion or damping functions similar in mechanical behavior to the removed intervertebral disc tissue. However, known elastomer discs experience long-term in-vivo problems stemming from micro-cracking, fixation problems with respect to the endplates, insufficient compression and torsional resistance, and excessive motion which can lead to bulging of the replacement disc and resultant pain for the patient. One hypothesis for the failures of previous elastomer based disc designs is the unlimited potential for strain. High load in vivo events cause subsequent changes in structural characteristics of the elastomer, a characteristic called the Mullins effect. After initial stress softening effects are accounted for, a stable stress strain

curve is reached. However, if a new load cycle is encountered exceeding the previous peak strain, the structural properties will again change. This is the rationale for the failure of previous elastomer disc designs and the inspiration for new motion-limited designs.

[0011] Ball and socket discs typically incorporate two plate members having cooperating inner ball and socket portions allowing an articulating motion of the members during movement of the spine. These types of discs generally restore spinal motion, but inadequately replicate the natural stiffness of the intervertebral disc. Furthermore, dislocation and wear problems exist with these devices as well as unsatisfactory motion limiting components. Some types also comprise polymers in conjunction with metallic components.

[0012] For example, a Link Charite disc includes polyethylene/cobalt chrome molybdenum (CCM) construction. This design restores motion, but in a very unphysiologic manner. The design is essentially a ball and socket joint which does not provide the nonlinear elastic response of the normal disc including hysteresis and therefore shock absorption. As in hip replacements this design is subject to wear and polyethylene debris complications. This disc, which has been extensively implanted in Europe and the United States, relies on a relatively incompressible ultra high molecular weight polyethylene center mating with concave surfaces in cobalt chrome upper and lower endplates. The mating surfaces provide a low friction pseudo ball-socket joint with motion constraints in compression and anterior-posterior as well as lateral translation. The device is totally unconstrained in rotation about its axis, and in tension. Though this device has a semi successful in vivo history, it lacks fundamental stress strain characteristics of the normal disc. Instead, it provides low friction, high movement, non-energy absorbing kinematic function restoration to the spine motion segment. The disc is designed to move freely until limits of travel are reached. The stopping action provided is very abrupt and thus loads the vertebral endplate in a shock-like manner at end-of-travel. This disc imitates a free moving ball and socket joint, not a natural disc that behaves very elastically until annulus fibers play the role of a "limiter". A natural disc is load sharing between the elastic elements and fibrous tissue limiters.

[0013] Mechanical spring discs, which generally have only two or three degrees of freedom, typically incorporate one or more coiled springs disposed between metal endplates. These discs generally allow movement of the vertebrae during flexion and extension. However, these types have significant wear problems, as well as problems

dealing with in-vivo torsional loads, and overall these discs cannot replicate the six-degree of freedom movement of a natural intervertebral disc.

[0014] Hybrid types of discs generally incorporate two or more principals of any of the aforementioned disc types. For example, one common hybrid disc arrangement includes a ball and socket set surrounded by a non-adhered elastomer ring. This hybrid disc is more complex than would be preferred for common usage, and more importantly, the intermittent contact between the ball socket and the elastomer ring that occasionally occurs in-vivo causes critical wear problems.

[0015] It is to be recognized that an artificial disc constructed with a polymer between two metal endplates undergoes compression as a result of both gravity and patient activities requiring exertion of energy. Therefore, ideally a disc would include a means of protecting the polymer and the possible bond joint between polymer and metal. Mechanical stops and motion-limiters can be added to maintain the integrity of the prosthesis. Such structures can take the form of rods, tension cables, or other connectors, as well as metal-to-metal contact in compression, to name but a few examples. Moreover, it would be beneficial for a disc also to include a means to convey to surgeons and to patients the actual state of the loads experienced by the device.

[0016] As a result, the need exists for an artificial intervertebral disc that more closely imitates a natural disc. This means that the artificial disc should maintain the vertebrae spaced from each other and prevent pinching of nerves or spinal cord. The artificial disc should provide good load distribution. Furthermore, the artificial disc should be sufficiently resilient to accommodate other motions of the spine, including flexion, extension, lateral bending, and rotation, as well as combinations of these motions. In humans, the bony facet joints actually limit the rotational movement. A disc typically need only rotate approximately three degrees. Moreover, the disc should provide restorative force to bias toward the resting position. The artificial disc should be both biocompatible and biostable such that the disc itself or any of its degradation byproducts, if any, do not cause adverse tissue reactions. Ideally, through the use of strain gauges or other means of force transduction, the disc can also provide stored or real-time data to the surgeon and the patient regarding the state of the loads and displacements experienced by the disc.

BRIEF SUMMARY OF THE INVENTION

[0017] The present invention is directed to a prosthetic intervertebral disc replacement that restores and preserves the physiologic function of a normal spinal motion segment. The intervertebral disc replacement addresses the detrimental phenomenon of cascading spine syndrome observed in long-term patients with fused-spinal segments. The present intervertebral disc replacement is designed to avoid the need for spinal fusion or at least prolong the need for it. The invention incorporates elements to bear high load in the design, while preserving the ability of the elastomer to provide substantial motion at low to moderate loads. The invention demonstrates the potential to survive high cycle fatigue in bending, compression, and shear along all three mutually orthogonal axes. The motion-limiting features survive high load, low cycle fatigue and preserve the integrity of the elastic range performance of the device.

[0018] According to the present invention, once the disc reaches its mechanically constrained limits in compression, bending, and shear, then the elastomer and the bond interface experiences no additional significant loads as the limiter feature will prevent further significant strain. In vivo loading varies by the individual, activity level, and unique high load events. In the present invention, limiting strains prevents the elastomer from continually changing its structural characteristics with each high load event. A stable stress strain characteristic can be reached and predictable disc performance can be achieved.

[0019] The present invention is a visco-elastic constrained-motion disc prosthesis generally comprising specially designed rigid upper and lower endplates having therewithin channels or openings for receiving one or more motion-limiting members fitted on each end with an enlarged portion. In some embodiments, the lower surface of the upper endplate contains a first projection therefrom that extends toward the lower endplate. Likewise, the upper surface of the lower endplate can contain a second projection extending toward said upper endplate and substantially aligned with said first projection. The first and second projections terminate to create a gap therebetween, forming a compression stop. Interposed between the upper and lower endplates is an elastomer cushion. Preferably, the elastomer cushion is not in direct contact with either the motion-limiting members or the first or second projections to avoid wear and debris problems.

[0020] The gap allows a predetermined amount of axial movement, but no more, between the upper endplate and the lower endplate. As a result, the gap prevents excess compression from occurring, and is usually designed to allow approximately 1 to 2 millimeters of relative movement between the upper and lower endplates. This limits the compressive stresses

seen by the elastomer. During most activities of the patient, the elastomer will exclusively carry the load. The compression stop will be engaged typically only during activities of high exertion.

[0021] The motion-limiting members with enlarged portions are inserted into internal cavities in the elastomer and link the upper endplate to the lower endplate. The motion-limiting members are dimensioned so as to have a length that is slightly greater than the distance between the lower surface of the upper endplate and the upper surface of the lower endplate (and also preferably slightly less than the overall length of the internal cavities in which they reside). This allows space for the motion-limiting members to move during compression.

[0022] In bending, which is the most important movement of an L4-L5 or L5-S1 disc, the motion-limiting members are strategically oriented to resist the tension in the posterior region of the disc. If motion-limiting members are present at the anterior portion of the disc, they float freely in the internal cavities during bending.

[0023] The external surfaces of the upper and lower endplates can also be fitted with wedges, spikes, keels, or other appurtenances to aid in attachment to a vertebral body. These appurtenances can also serve as covers to enclose the enlarged portions of the motion-limiting members.

[0024] Additionally, some embodiments of the invention utilize strain gauges, pressure transducers, piezoelectric force transducers, or other means of force transduction to provide stored or real-time data to the surgeon or patient of the load state of the disc.

[0025] Several commercially available low durometer (i.e., approximately 70-85A) polyurethanes with a history of animal and human implantation are candidates to be used in a titanium or CoCrMo/elastomer construction. Hybrid discs according to the invention can overcome one of the failure modes of previous artificial disc designs, namely that of delamination and fatigue failure of the bonded interface between the elastomer and metal. This can be accomplished through improved bonding and motion-limiting features, in those embodiments where the visco-elastic cushion is bonded to the endplates. Other embodiments that utilize no bonding between the visco-elastic cushion and the endplates also achieve improved results with motion-limiting features.

[0026] These and other benefits are obtained in the many embodiments of the invention. A particularly useful embodiment comprises an artificial intervertebral disc prosthesis having an anterior portion and a posterior portion, further comprising: a first endplate

having an upper surface and a lower surface, wherein the first endplate further comprises at least one opening for receiving at least one motion-limiting member; a first projection extending from the lower surface of the first endplate terminating in a first distal end; a second endplate having an upper surface and a lower surface, wherein the second endplate further comprises at least one opening for receiving at least one motion-limiting member; a second projection extending from the upper surface of the second endplate and substantially aligned with the first projection, wherein the second projection terminates at a second distal end to form a gap having a predetermined distance between the first and second distal ends; at least one motion-limiting member received respectively in the at least one opening of the first and second endplates, linking the two endplates and allowing only a predetermined amount of movement thereof; and a visco-elastic cushion between the first endplate and the second endplate, further comprising therein at least one cavity in substantial alignment with the at least one opening in the first endplate and the second endplate through which the motion-limiting member may pass and at least one cavity surrounding the first and second projections.

BRIEF DESCRIPTION OF THE DRAWINGS

[0027] The teachings of the present invention can be readily understood by considering the following detailed description in conjunction with the accompanying drawings, in which:

[0028] Figure 1 is a graph showing the typical nonlinear response to load of human spine motion segments;

[0029] Figure 2 is a diagram showing a reference coordinate system for a functional spinal unit to be used herein;

[0030] Figure 3 is a posterior perspective view of a first embodiment of an artificial disc of the present invention.

[0031] Figure 3(a) is the artificial disc of Figure 3 showing a second type of appurtenance fitted to the upper and lower endplates;

[0032] Figure 3(b) is the artificial disc of Figure 3 showing a third type of appurtenance fitted to the upper and lower endplates;

[0033] Figure 3(c) is the artificial disc of Figure 3 showing a fourth type of appurtenance fitted to the upper and lower endplates;

[0034] Figure 4 is a top plan view of the artificial disc of Figure 3;

- [0035] Figure 5 is a bottom plan view of the artificial disc of Figure 3;
- [0036] Figure 6 is a posterior elevation view of the artificial disc of Figure 3;
- [0037] Figure 7 is a lateral elevation view of the artificial disc of Figure 3;
- [0038] Figure 8 is an exploded perspective view of the artificial disc shown in Figure 3;
- [0039] Figure 9 is a section view taken along plane A-A in Figure 3;
- [0040] Figure 10 is a section view taken along plane B-B in Figure 3;
- [0041] Figure 11 is a section view taken along plane C-C in Figure 3;
- [0042] Figure 12 is a section view taken along plane D-D in Figure 3;
- [0043] Figure 13 is an exploded perspective view of an exemplary motion-limiting member of a first embodiment of the invention;
- [0044] Figure 14 is a perspective view of a second embodiment of an artificial disc of the present invention having four motion-limiting members therein;
- [0045] Figure 15 is an exploded perspective view of the embodiment of the artificial disc of the present invention shown in Figure 14;
- [0046] Figure 16 is a section view taken along plane E-E in Figure 14;
- [0047] Figure 17 is a section view taken along plane F-F in Figure 14;
- [0048] Figure 18 is a section view taken along plane G-G in Figure 14;
- [0049] Figure 19 is a section view taken along plane H-H in Figure 14;
- [0050] Figure 20 is a section view taken along plane I-I in Figure 14;
- [0051] Figure 21 is a side elevation view of a disc according to a first embodiment of the invention showing the disc in normal bending mode;
- [0052] Figure 22 is a top view of an embodiment of a lower endplate flex circuit for an artificial disc using strain gauges to provide force transduction for providing data external to the disc;
- [0053] Figure 23 is a side section view of the disc shown in Figure 21 in normal bending mode;
- [0054] Figure 24 is a perspective view of a motion-limiting member according to an embodiment of the invention incorporating a split ring in place around the enlarged portion of the motion-limiting member;
- [0055] Figure 25 is a side elevation schematic of an embodiment of an artificial disc using strain gauges to provide force transduction for providing data to locations external to the disc;

[0056] Figure 26 is a perspective view of the posterior side of an alternative embodiment of the disc showing removable appurtenances;

[0057] Figure 27 is a perspective view of the anterior side of the disc shown in Figure 26;

[0058] Figure 28 is a perspective view of the posterior side of an appurtenance and an upper endplate according to an embodiment of the invention; and

[0059] Figure 29 is a perspective view of the anterior side of the endplate shown in Figure 28.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

[0060] While the present invention will be described more fully hereinafter with reference to the accompanying drawings, in which particular embodiments and methods are shown, it is to be understood from the outset that persons of ordinary skill in the art may modify the invention herein described while achieving the functions and results of this invention.

Accordingly, the description which follows is to be understood as illustrative and exemplary of specific embodiments within the broad scope of the present invention and not as limiting the scope of the invention. In the following descriptions, like numbers refer to similar features or like elements throughout.

[0061] A successful intervertebral disc prosthesis should restore and preserve physiologic function of a normal spinal motion segment. Figure 1 is a graph of the response of the normal human disc to load. The nonlinear response of the motion segment is a function not only of the disc, but of the facet joints and ligaments. Facet joint function and ligamentous structures may be compromised and unable to provide load sharing as in a normal motion segment. The nonlinear response of spine motion segment to load shown in Figure 1 is a typical curve shape in compression, shear, torsion, and bending.

[0062] Figure 2 is a perspective view of a reference intervertebral disc coordinate system that will be used throughout this discussion for ease of reference. The figure shows typical loads (forces and moments) and typical displacements (translation and rotation) that can occur in each of the three mutually orthogonal directions. The load-deflection curve shape of Figure 1 is similar in all three directions for a normal disc. Like that of a normal disc, a disc 10 of the present invention provides a nonlinear response to torsion, shear, and compressive loads.

[0063] Referring now to Figure 3, the disc 10 comprises a first or upper endplate 20, a second or lower endplate 30, and a visco-elastic cushion 40 interposed between and adhered

to the two endplates. The upper and lower plates 20, 30 are substantially symmetrical about an anterior-posterior horizontally extending plane (a transverse plane shown in Figure 2), as well as about a sagittal plane (Figure 2). The terms "upper" and "lower" are used herein only for illustration purposes with reference to the orientation of the disc 10 when it is implanted in the human body between two adjacent vertebrae V1 and V2 (defined as the cephalad-caudal direction in Figure 2). Indeed, the upper plate is more generally described as a first plate and the lower plate is more generally described as a second plate.

[0064] The upper endplate 20 is rigid and is preferably made from a biocompatible material such as stainless steel, titanium, titanium alloys (such as Ti6Al4V), composite materials, and the like. The most preferred material is cobalt chrome molybdenum (CoCrMo or "CCM") comprising approximately 66% Co, 28% Cr, and 6% Mo by weight.

[0065] The upper endplate 20 has an upper surface 21 and a lower surface 22 and an anterior portion 23 and a posterior portion 24. Upper surface 21 and lower surface 22 are generally parallel. The anterior portion 23 is the portion of the upper endplate 20 that is disposed anteriorly in the spine when the disc 10 is implanted. Likewise, the posterior portion 24 is the portion of the upper endplate 20 that is disposed posteriorly in the spine when the disc 10 is implanted. The upper endplate 20 has an external surface 29 therearound that preferably defines a generally "D" shape. In one embodiment of the invention, the posterior portion 24 of the external surface 29 has a concavity 28 therein that defines posterior lobes 25, 26 projecting from the posterior portion 24 (see Figures 3, 4, 5, 12, 14, and 15). One or more appurtenance 27 may be optionally affixed to the upper surface 21 to facilitate attachment.

[0066] The upper endplate 20 likewise may comprise an upper subplate 200 (see Figure 15) that can be formed monolithic with the upper endplate 20 or as a separate component affixed thereto subsequent to manufacture. Alternatively, the structures that comprise the upper subplate 200 may simply be included in the upper endplate 20. The remainder of this description will discuss structure related to subplate 200, but it should be recognized that the description applies equally to discs having no separate subplate. The subplate 200 further comprises an upper surface 210 and a lower surface 220 and an anterior portion 230 and a posterior portion 240. A first projection 270 optionally may depend from the lower surface 220 of the subplate 200 to act as part of a compression stop, as will be described below. The upper subplate 200 also has a plurality of openings 271 therethrough for receiving one or more motion-limiting members 80 (described below). Preferably, the upper subplate 200

includes two openings 271, one disposed posteriorly and slightly to the left (in the medial-lateral plane) of the first projection 270 and another disposed posteriorly and slightly to the right (in the medial-lateral plane) of the first projection 270 (assuming the center of rotation is at the geometric center of the disc). The openings 271 further comprise a bearing surface 272 for interacting with the motion-limiting members 80 or a split ring assembly 400 (described below). The bearing surface 272 is preferably a tapered opening having a larger diameter at the upper surface 210 than at the lower surface 220. The taper can be linear or nonlinear, including conic sections, parabolic sections, spherical sections, and so forth, to name only a few examples.

[0067] The first projection 270 preferably extends from said lower surface 220 a height of approximately 1 mm to approximately 3 mm. Many shapes are possible for the first projection 270, and indeed multiple projections, or no projections, are contemplated as well. In the preferred embodiment, the first projection 270 takes the form of a substantially cylindrical section having a slight radius on its terminal end of approximately 2 mm to approximately 15 mm, preferably approximately 8 mm to approximately 12 mm.

[0068] In like manner, the disc 10 further comprises a lower endplate 30. The lower endplate 30 is rigid and is preferably made from a biocompatible material such as stainless steel, titanium, titanium alloys (such as Ti6Al4V), composite materials, and the like. The preferred material is cobalt chrome molybdenum (CCM) comprising approximately 66% Co, 28% Cr, and 6% Mo by weight, respectively.

[0069] The lower endplate 30 has an upper surface 31 and a lower surface 32 and an anterior portion 33 and a posterior portion 34. Upper surface 31 and lower surface 32 are generally parallel. The anterior portion 33 is the portion of the lower endplate 30 that is disposed anteriorly in the spine when the disc 10 is implanted. Likewise, the posterior portion 34 is the portion of the lower endplate 30 that is disposed posteriorly in the spine when the disc 10 is implanted. The lower endplate 30 has an external surface 39 therearound that preferably defines a generally "D" shape. In one embodiment of the invention, the posterior portion 34 of the external surface 39 has a concavity 38 therein that defines posterior lobes 35, 36 projecting from the posterior portion 34 (see Figures 3, 4, 5, 12, 14, and 15). One or more appurtenance 37 may be optionally affixed to the lower surface 32 to facilitate attachment.

[0070] Although not preferred, it is possible that the lower endplate 30 may comprise a lower subplate 300 (see Figures 8 and 15) that can be formed monolithic with the lower

endplate 30 or as a separate component affixed thereto subsequent to manufacture. The subplate 300 further comprises an upper surface 310 and a lower surface 320 and an anterior portion 330 and a posterior portion 340. A second projection 370 depends from the upper surface 310 of the subplate 300 to act as part of a compression stop, as will be described below. The lower subplate 300 also has a plurality of openings 371 therethrough, having bearing surfaces 372, for receiving one or more motion-limiting members 80 (described below). Preferably, the lower subplate 300 includes two openings 371, one disposed posteriorly and slightly to the left of the first projection 370 and another disposed posteriorly and slightly to the right of the first projection 370.

[0071] The second projection 370 preferably extends from said upper surface 310 a height of approximately 3 mm to approximately 6 mm. Preferably the second projection 370 is in substantial alignment with the first projection 270. Stated otherwise, the second projection 370 preferably will have its longitudinal axis aligned with or close to the longitudinal axis of the first projection 270. This is not mandatory, however. Indeed, the two projections 270, 370 may be offset from one another, it being more important that at least a portion of the projections 270, 370 overlap during contact therebetween. And, depending on the respective shapes of the projections 270, 370, the amount of offset may vary. Many shapes are possible for the second projection 370, including, but not limited to, all regular polygonal shapes. Additionally, the projections 270, 370 may take the form of partial polygons (for example, a half cylinder or a partial elliptical cylinder, to name but a few). In the preferred embodiment, the second projection 370 takes the form of a cylindrical platform having a diameter of approximately 6 mm to 10 mm, and more particularly, approximately 7 mm to approximately 9 mm.

[0072] Referring now to Figures 8, 9, 12 and 13, a motion-limiting member 80 typically resides within each opening 271, 371. Each motion-limiting member 80 has a length 81 and a diameter 82, and a first end 83 and a second end 84. At each end 83, 84 is an enlarged portion 90. The motion-limiting members 80 link the upper endplate 20 to the lower endplate 30 and assist in handling the loads associated with flexion, as will be described below.

[0073] The motion-limiting members 80 can be any of several longitudinal rod-like members, both rigid and semi-rigid, including solid metallic bars or rods of varying cross-sections, and wire. If wire is used as the motion-limiting member 80, the motion-limiting members 80 typically have diameters of approximately 0.038 inches to approximately 0.080

inches. However, the number of motion-limiting members 80 used plays a role in determining the diameter of each motion-limiting member 80. In the preferred embodiment, there are two motion-limiting members 80 that are braided metal wires, preferably a braided stainless steel wire having a diameter of approximately 0.062 inches and a rated tensile strength of approximately 320 pounds. More specifically, the motion-limiting members 80 can be of any material described above, but are preferably cables of 316L stainless, MP35N, Haynes 25. In alternative, though less preferred, embodiments where substantially more numerous motion-limiting members 80 are used (for example ten to twenty), the diameters can be significantly smaller.

[0074] The enlarged portion 90 at each end 83, 84 is typically a spherically-shaped structure, or ball 91, that is affixed to the motion-limiting member 80. Balls 91 are preferably of the same material as the motion-limiting members 80. The ball 91 has an upper surface 92 and a lower surface 93. Preferably, ball 91 is preformed onto the motion-limiting member 80. However, methods of fixation are also varied and include welding, both during formation of the ball 91 at the first end 83 and during assembly of the ball 91 at the second end 84; as well as crimping on a ball 91. The balls 91 are preferably hemispheres wherein the lower surface 93 engages the bearing surface 272 of the plates 20, 30 and/or the subplate 200, 300. The upper surface 92 of the ball 91 provides little to no advantage and merely takes up space. As a result, the upper surface 92 is preferably flat or very low-profile so as to take up a minimal amount of space. The appurtenances 27, 37 on the upper and lower endplates 20, 30, respectively, may be used to cover a portion of the enlarged portions 91. In some embodiments, however, the inside surface 400d of the split ring assembly (described below) can be used to effectively shorten the length of the motion-limiting member 80 such that no part of the enlarged portion 91 extends beyond the upper surface 21 of the upper endplate or the lower surface 32 of the lower endplate 30.

[0075] In the preferred embodiment, a split ring assembly 400, as shown in Figures 8, 13, 15, and 24, fits into the openings 271 of the upper subplate 200 and into openings 371 of the lower subplate 300. The split ring assembly 400 comprises a first half 400a and a second half 400b. When the two halves 400a, 400b of the split ring assembly 400 are combined, they form a ring-shaped member having a port 400c defined by a periphery 400e. The split ring assembly 400 includes an inside surface 400d that serves as a bearing surface against which the balls 91 can articulate, resulting in a mini-ball and socket joint. The diameter of port 400c is smaller than that of the ball 91. Thus, when assembling the artificial disc

prosthesis, the motion-limiting member 80 is inserted into the opening 271 of the upper subplate 200 at the first end 83 and into the opening 371 of the lower subplate 300 at the second end 84. The first half 400a of the split ring assembly 400 is then inserted into the opening 271 underneath the ball 91 at the first end 83 of the motion-limiting member 80. Then, the second half 400b of the split ring assembly 400 is inserted into the opening 271 of the upper subplate 200 underneath the ball 91 at the first end 83 of the motion-limiting member 80, completing the split ring assembly 400 in the upper subplate 200. Since the diameter of the port 400c in the split ring assembly is smaller than that of the ball 91 at the first end 83 of the motion-limiting member 80, the motion-limiting member 80 is prevented from slipping through the opening 271 of the upper subplate 270.

[0076] In the same manner, a split ring assembly 400 is inserted into the opening 371 of the lower subplate 300 above the ball 91 at the second end 84 of the motion-limiting member 80 in order to prevent the motion-limiting member 80 from slipping through the opening 370 of the lower subplate 300. Once the split ring assemblies 400 are in place, they may be welded or permanently affixed by some other means known in the art to the upper and lower subplate assemblies 200, 300. The split ring assembly 400 includes an inside surface 400d that serves as a bearing surface against which the balls 91 can articulate, resulting in a mini-ball and socket joint, thus minimizing the bending of the motion-limiting member 80 and extending fatigue life.

[0077] In another embodiment, the split ring assembly 400 is not present, and the balls 91 are not preformed onto the motion-limiting members 80. Instead the balls 91 are fixed onto the motion-limiting members 80 through some other means such as welding or crimping, as discussed above. However, welding the ends of the motion-limiting members 80 into balls 91 can lower the strength of the motion-limiting members 80 by 10 to 15 percent. In this embodiment, the diameter of ball 91 can be controlled during welding, ranging in size from approximately slightly larger than the diameter of the motion-limiting member 80 up to a maximum diameter of approximately two times the motion-limiting member diameter. In embodiments using other attachment methods, other diameters are possible. Since no split ring assembly 400 is present in this embodiment to prevent the motion-limiting members 80 from slipping out of the openings 271, 371 of the upper and lower subplates 200, 300, respectively, it is necessary that the diameter of the balls 91 be larger than the diameter of the opening 271 at the lower surface 220 of the upper subplate 200 and the opening 371 at the upper surface 310 of the lower subplate 300.

[0078] In the embodiments containing no split ring assembly, the balls 91 at the first end 83 and the second end 84 mate with the bearing surface 272 of the openings 271 in each endplate 20, 30 and/or subplate 200, 300. As a result, each union of ball 91 and bearing surface 272 results in a mini-ball and socket joint that allows articulation of the ball 91 and motion-limiting member 80 within the opening 271, thus limiting bending of the motion-limiting member 80, thereby extending fatigue life.

[0079] The disc 10 of the preferred embodiment provides motion-limiting features in compression and bending, thereby behaving in vivo in a fashion more similar to a natural spinal disc. The first projection 270 and the second projection 370, by way of the predetermined gap 470 therebetween (see Figures 9, 10, 11, 16, 17, and 19), provide a compression stop preventing movement between the upper and lower plates 20, 30 in a magnitude greater than a predetermined amount. Varying limits of movement may be set, depending on the type and location of the disc 10 in the body. In the preferred embodiment, the gap 470 between the first and second projections 270, 370 is approximately 1 to 2 millimeters. Elastomers that can handle excessive compressive loadings may be able to accommodate a gap greater than 2 millimeters. Once a compressive load is applied to the disc 10, the visco-elastic cushion 40 absorbs the compression in a visco-elastic fashion according to design properties of the elastomer. Upon absorbing the compressive loads in amounts sufficient to cause relative movement between the upper endplate 20 and the lower endplate 30 in an amount equal to the gap 470, the first and second projections 270, 370 then come into contact and prevent further compressive loads from being applied to the elastomer. It is expected that the stop mechanism will only be activated during the most strenuous of activities of the patient.

[0080] In bending, the motion-limiting members 80 can perform the primary or secondary motion limiting functions. Referring to Figure 2, the most common bending scenario for the spine is bending in the sagittal plane (that is, bending about the x-axis). For example, this would be accomplished by bending over to tie one's shoes. As a bending moment is applied to the disc 10, the disc 10 can undergo both shear and lateral displacement. Referring now to Figures 21 and 23, a disc 10 is depicted in such a scenario and is shown exaggerated for easier reference. It can be seen that the anterior side is slightly compressed, while the posterior side is slightly in tension and a slight translation of the upper endplate 20 with respect to the lower endplate 30. It can be seen that the motion-limiting members 80 can become oriented diagonally. In this event, the motion-limiting members 80 in tension

provide a force preventing the upper endplate 20 and lower endplate 30 from separating because the lower surface 93 of the ball 91 begins to bear upon the split ring assembly 400 and/or bearing surfaces 272 of the openings 271. It should be noted that the mechanics of the disc 10 depicted in Figures 21 and 23, with reference to Figure 2, are basically identical whether the bending is in the sagittal plane (front to back, or tying ones shoes) or in the frontal plane (side to side bending).

[0081] In flexion, which is the most important movement of an L4-L5 or L5-S1 disc, the motion-limiting members 80 are strategically oriented to resist the tension in the posterior region of the disc 10. When braided cables are used as the motion-limiting members 80, compression of the cables can cause splaying, which shortens their fatigue life. Therefore, placing more motion-limiting members 80 posteriorly than anteriorly (for example, see Figure 12) accounts for the greater expected flexion moments of 20-30 N·m versus the lesser extension moments of about 10 N·m.

[0082] A further factor in the allowed range of motion in flexion and extension is a consideration of the cable distance from an assumed center of rotation at the center of the disc 10. The farther from the center, the greater the resisting moment, but the more initial slack necessary to allow the required 8-12 degrees of flexion. The more initial slack allowed, the more bending movement is allowed. Combinations of cable placement and initial diagonal orientation may be necessary to solve these conflicting design goals. Although greater ranges are certainly possible for the invention, preferable ranges of stiffnesses and motion for the disc 10 are as follows: Nonlinear stiffness in compression (1,000 to 3,000 N/mm) and in flexion (1.0 to 5.0 N·m/deg) and maximum motion in compression (1.0 to 2.0 mm) and in flexion (8 to 12 deg).

[0083] In one embodiment of the artificial intervertebral disc prosthesis (see Figures 14, 15, 16, 17, 18, and 19), four motion-limiting members are present. In this embodiment, there are corresponding four openings 271, 371 in both the upper and lower subplates, 200, 300. One of the openings 271, 371 is located anteriorly and slightly to the left of the first and second projections 270, 370, while another opening 271, 371 is located anteriorly and slightly to the right of the first and second projections 270, 370. Similarly, a third opening 271, 371 is located posteriorly and slightly to the left of the first and second projections 270, 370, while the fourth opening 271, 371 is located posteriorly and slightly to the right of the first and second projection 270, 370. In this embodiment, when the disc 10 is in flexion, the most important movement of an L4-L5 disc, the motion-limiting members 80 at the

posterior portion of the disc 10 are strategically-oriented to resist the tension in the posterior region of the disc 10, while the motion-limiting members 80 at the anterior portion of the disc 10 float freely in the spike cavity in the anterior region of the disc 10. However, a disadvantage of this embodiment is the presence of motion-limiting members 80 at the anterior portion of the disc 10. As discussed above, when braided cables are used for the motion-limiting members 80, compression can cause splaying, leading to a shorter fatigue life. As motion-limiting members 80 located at the anterior of the disc 10 encounter significantly more compression than motion-limiting members 80 located at the posterior of the disc 10 during the normal activity patterns of most individuals, anteriorly-located motion-limiting members 80 are likely to have a shorter life than those located at the posterior of the disc 10.

[0084] Another embodiment of the artificial disc intervertebral prosthesis is envisioned in which no motion-limiting member 80 is present. Instead, the compression stop formed by the first and second projections 270, 370 also limits motion in flexion and lateral bending. This is accomplished by sizing the first and second projections 270, 370 such that when the prosthesis engages in flexion or bending and the first projection 270 tilts toward the second projection 370, the leading edge of the first projection 270 will come into contact with the second projection 370 after a predetermined amount of flexion or bending, preventing further motion. This has the advantage of eliminating the need for the motion-limiting members 80, thereby reducing the number of elements within the prosthesis that are susceptible to wear and fatigue.

[0085] The preferred disc has certain load versus deflection characteristics that are similar to those found in the natural human disc. As was stated above, it is useful, once implanted, that the surgeon and patient can know the state of load experienced by the device. In this regard, embodiments of the disc have, integral to its construction, strain gauges or other means of force or pressure transduction. For illustration purposes only, not to be construed as limiting the invention thereto, the discussion will be directed to the use of strain gauges. A transducer can be connected to signal conditioning and amplification circuitry on a micro scale in order to fit within the constraints of space available in the upper or lower endplate. In this embodiment, the center stop is integral to the lower endplate and consists of a hollow raised cylindrical platform. The space inside this cylinder can house, for example, a 3 x 3 x 3 mm electronics package. The package can be wired to strain gauges on the inside of the raised cylinder and in peripheral locations around the bottom endplate. Alternatively, the

transduction means can be connected to electronics such as piezoelectronics that eliminate the need for signal conditioning and amplification.

[0086] Since the center stop cylinder is not in contact with the polymer, the strain gauge placed there will only measure contacts between the upper endplate and the center stop on the lower endplate. This data is useful in itself as an indicator of when loads are sufficiently high to engage the stop mechanism. However, in addition, more continuous data is available from peripherally placed strain gauges that will measure stress in the endplate caused by compression, bending, torsion, and shear loads in all directions. This information can give a precise measure of the magnitude and direction of loads on the disc. Figures 22 and 25 depict how one embodiment of an artificial disc 10 uses strain gauges to measure the load experienced by the prosthesis and relay that data on demand.

[0087] Placing the transducers within the polymer is not preferred since fatigue of wires or the introduction of stress risers within the polymer can lead to fatigue failure initiation sites. For these reasons, placing the signal conditioning microelectronics within the center compression stop is advantageous. Once conditioned, the signal is telemeterized on demand through excitation of an internal coil from an inductively coupled external coil. This couple energizes the electronics and transmits the data upon request. This mode of interrogating the device for its load condition can be done real time or fed back from memory storage according to a preset sampling routine. It is also possible to sample the device remotely and wirelessly via the internet.

[0088] The data can indicate changes in the device since its implantation. It can also store load history to indicate if the patient is following doctor's orders for allowed activities. The power source for memory-based data is optionally a micro battery or a capacitor charged from the external inductive couple. The use of piezos is also possible. In one embodiment, a mylar flex circuit is pre-made and placed on the second endplate. Transducers are embedded on the mylar circuit and connected to the signal conditioning and amplifying electronics.

[0089] Figures 26-29 show an alternative embodiment of the invention wherein the disc 10 comprises multiple components that may be implanted separately. Indeed, the disc 10 may comprise many forms and embodiments that are implantable in pieces. The desirability of multi-part prostheses is known by surgeons and simplifies the implantation procedures. Figures 26-29 simply depict one example. In these figures, the appurtenances 27 are removably insertable into the upper and lower endplates 20, 30. In Figure 26 the upper

surface 92 of the balls 91 is not depicted but typically would be visible. Preferably, the groove into which appurtenances 27 are slid form a taper lock fit to lock the appurtenance into place. One example of a surgical procedure using a multi-part disc 10 involves the surgeon first removing the diseased or damaged disc using the typical procedures in practice. An instrument (not shown) is used to prepare the site by cutting grooves into the adjacent vertebrae to receive the appurtenances 27 of the disc 10. Preferably the instrument cuts both the upper and lower grooves simultaneously so as to maintain the tolerances needed for the implantation of the disc 10. An instrument then inserts the appurtenances 27 into the prepared site. The disc 10 is then inserted between the appurtenances 27, which receive the grooves of the upper and lower endplates 20, 30. The taper lock secures the appurtenances 27 to the prosthesis.

[0090] Many possibilities exist for the manufacturing and the materials involved in an artificial intervertebral disc prosthesis according to the present invention. The endplates 20, 30 and/or endplate subplates 200, 300 may be of the materials described above. Further, they may have thicknesses in the range of approximately 1 mm to approximately 3 mm. Their surfaces may be surface-treated or machined for texture and bonding improvement. Examples of such treatments include but are not limited to ion etching, simple grit blasting, plasma spraying, or CNC machined geometry. Preferably the endplates 20, 30 (and/or 200, 300) are a CCM which is good in wear. The upper surfaces 21, 210 of the upper endplate 20 and upper subplate 200, and the lower surfaces 31, 310 of the lower endplate 30 and lower subplate 300, as well as the surfaces that interact with the visco-elastic cushion, may be coated with Titanium 6Al4V to improve bone interface and bonding. The second projection 370 can, as stated above, take many forms, including by way of mere examples, a cylinder, a post, a platform, and so forth. The preferred cylindrical member is a solid projection from the lower endplate 20 or lower subplate 200. However, the cylindrical member could be hollow so as to accommodate integral microelectronics diagnostics, as was discussed above.

[0091] Manufacturing the disc 10 can be accomplished in a variety of manners. Preferably, the endplates 20, 30 are first machined of either titanium or cobalt chrome molybdenum (CCM), with openings 270 representing areas where there will be no elastomer cushion 40. The endplates 20, 30 are inserted into a mold with cores to create voids that will later contain the center stop and the motion-limiting members 80. It is preferable to keep the elastomer free of the cables and center stop so as not to introduce

elastomer abrasion leading to fatigue failures. The motion-limiting members 80 are then assembled to the molded subassembly with a welding process. The cable assemblies terminate in a ball end. In the preferred embodiment the ball is preformed onto the cable, though this is not required.

[0092] These ball-cable assemblies are then inserted into the endplates 20, 30 with the split ring assemblies 400 as described above. In those embodiments not utilizing split ring assemblies 400, the ball-cable assemblies are inserted into the endplates 20, 30 as described above. Preferably, over each ball location on the upper endplate 20 and on the lower endplate 30 are appurtenances 27, 37, respectively. These appurtenances are shown in Figure 3 as keels, but they could be individual conical spikes as shown in Figure 3(a) or other appurtenances, for example Figures 3(b) and 3(c). For those embodiments where the enlarged portion 90 extends beyond the plane of the upper surface 21 of the upper endplate 20 or the lower surface 32 of the lower endplate 30, these appurtenances serve as temporary anchors in the vertebra and covers that enclose the mini ball-socket joint created between the endplate and the ball. Additionally, the ball-socket articulation prevents bending in the cables, thereby extending fatigue life. In certain embodiments utilizing many motion-limiting members 80, it is possible for the motion-limiting members 80 to be laser welded into the endplates in the openings where cores created voids in the elastomer.

[0093] As stated above, the center stop is a designed gap preferably to prevent more than 1-2 mm of compression from occurring, thereby limiting the elastomer compressive stress. This mandates a good wear interface for the stop. A choice of CCM on CCM is preferred due to its recent introduction as the wear couple in some FDA-approved metal-on-metal hips. Also as stated, many structural configurations for the first and second protrusions 270, 370 are possible, including pin-on-pin, pin-on-plate (shown), plate-on-plate, ball-on-plate, and so forth. The elastomer will exclusively carry the load during most activities of daily living. The center stop will be engaged only during activities of high exertion, except in the embodiment in which no motion-limiting members 80 are present.

[0094] While there has been described and illustrated particular embodiments of a novel artificial disc prosthesis, and in particular, a visco-elastic constrained motion disc, it will be apparent to those skilled in the art that variations and modifications may be possible without deviating from the broad spirit and principle of the present invention, which shall be limited solely by the scope of the claims appended hereto.